


圆锥滚子

Tapered Roller




圆锥滚子外形尺寸
Tapered Roller Overall Dimension

单位Unit: μm

直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ
11.4	16	45'	17.22	31.08	1°5'	20.15	25	56'
11.66	21.76	1°16'	17.5	31	1°10'	20.4	33	48'
12.07	16	1°21'	17.5	40	53'	20.5	21	3°52'
12.39	26.3	1°45'	17.65	35	1°5'	20.52	35	1°
13.436	23.5	45'	17.7	35	1°5'	20.55	46.08	51'
13.5	25	1°	17.72	36.5	55'	20.65	35	50'
13.7	16.27	1°12'	17.9	30.5	45'	20.67	32	1°
13.8	28	55'	18	31	1°6'	20.7	35	1°15'
14	24.07	1°13'	18.1	31	42'	20.8	35	1°25'
14.35	27.06	56'	18.1	41	0°50'	21.1	48	1°15'
14.46	28	1°	18.2	30	1°15'	21.22	35	50'
14.53	28	1°30'	18.2	38	56'30"	21.34	26.1	1°14'4"
14.53	25.2	45'	18.3	32	1°15'	21.45	24	1°45'
14.88	30	50'	18.36	42	30'	21.8	43	35'
14.9	24	1°10'	18.4	30	1°10'	22	33.9	0°50'
14.9	30	50'	18.45	38	50'	22.05	50	55'
15.2	25	1°	18.6	36.09	1°5'	22.157	42.5	55'10"
15.3	32	55'	19.03	36	1°6'	22.202	44.21	55'
15.368	21	1°10'	19.1	41	45'	22.24	30.5	30'
15.5	32.07	1°	19.18	19	2°10'	22.25	28.13	1°20'
15.547	32.9	1°8'	19.4	26	1°26'	22.35	41.08	51'
15.7	32.5	1°	19.5	46.5	1°15'	22.4	26.7	30'20"
15.8	33	1°5'	19.65	41.77	47'	22.45	41	52'30"
16	34	1°5'	20	32	1°9'	22.54	43.1	58'
16.15	35	1°5'	20	41.06	0°44'	22.6	32	2°47'
16.67	16.8	3°30'	20.05	36	1°5'	22.8	42	55'
17	31.09	1°10'	20.1	24.61	1°17'	22.9	36	3°30'
17	32.5	55'	20.1	35.1	1°10'	23	40	1°54'
17.08	17.08	55'	20.11	20	3°30'	23	53	1°

圆锥滚子

Tapered Roller



圆锥滚子外形尺寸


Tapered Roller Overall Dimension

单位Unit: μm

直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ
23.37	45	1°	25.6	48	55'	28	50	1°30'
23.579	53.2	1°10'	25.62	42.87	1°30'	28.05	38	1°18'
23.92	32.14	1°20'	25.7	50.1	56'	28.35	54.13	1°5'
23.96	27.5	53'40"	25.8	45.12	1°2'	28.5	30	4°18'
24	38.18	1°41'	25.8	70	1°	28.5	34	5°24'
24.05	40	1°7'	26	50	1°6'	28.6	62.1	46'
24.08	53	1°5'	26	52	56'	28.68	65.1	46'
24.1	34	1°10'	26	52.11	0°56'	28.7	60	50'
24.1	36.5	45'	26	56	46'20"	28.885	31	2°
24.1	42.5	1°	26.024	52	51'	28.91	30.25	2°
24.24	51.02	50'	26.08	54.1	0°51'	29	32	1°10'
24.25	54	52'	26.1	49	46'	29.1	44.7	1°33'
24.5	44	1°5'	26.347	52.5	55'	29.2	54	1°
24.74	47.5	1°10'	26.35	45	1°5'	29.3	39	1°15'
24.8	46	50'	26.4	33	1°50'	29.4	50	1°
24.96	46	1°35'	26.56	45	55'	29.5	30	1°27'
25	31.11	1°3'	26.7	46	47'	29.6	45	1°10'
25	41.5	1°2'	26.8	34.59	0°48'	29.7	48	1°6'
25	42.5	1°	27	39	1°20'	29.8	52.5	1°32'
25	42.5	1°	27.1	49	49'	29.9	48	1°
25	43.2	45'	27.2	49.13	1°4'	30.1	35.18	1°20'
25	43.5	1°	27.5	48	1°30'	30.2	56	1°50'
25	47	45'	27.5	53	1°20'	30.4	35.19	1°25'
25.15	45.61	1°2'	27.55	56	1°	30.55	54.11	48'
25.2	44.12	1°7'	27.7	51	1°5'	30.6	53.11	50'
25.33	50	0°51'	27.8	40.114	6°42'	30.7	57	50'
25.4	30.19	1°45'	27.97	31.93	1°30'	30.8	60.3	55'
25.5	45	1°5'	28	32.632	5°10'	30.96	62	55'
25.6	45	1°25'	28	46	1°15'	31	57.5	1°

圆锥滚子

Tapered Roller



圆锥滚子外形尺寸


Tapered Roller Overall Dimension

单位Unit: μm

直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ
31	70	50'	34.21	78.5	36'	37.36	42	1°15'
31.1	53.2	1°15'	34.3	38.37	2°20'	37.45	37.5	1°
31.2	36	1°20'	34.5	42	1°20'	37.6	46.66	1°
31.3	56	57'	34.6	60	1°1'	37.9	50	1°20'
31.42	41	1°	34.782	65.6	1°	38.05	50	1°
31.5	56.5	1°5'	34.86	70.2	1°20'	38.1	74.62	42'
31.62	34	1°45'	34.86	65	45'	38.1	65	1°15'
31.7	56.5	2°	34.9	45	1°25'	38.2	74.5	56'33"
31.8	56.5	58'	34.9	59	1°30'	38.3	78	46'
31.96	53	1°15'	35	57	56'	38.3	47	1°27'
32	36	1°15'	35	60	1°	38.4	69.14	50'
32	54	1°17'	35	64.5	1°25'	38.4	45.18	1°5'
32.1	39.15	1°5'	35.1	44	1°30'	38.7	72	1°24'
32.2	48	1°12'	35.2	60	50'	38.8	70.74	1°25'
32.47	65	53'	35.4	42	1°10'	39	62	1°7'
32.8	43.5	1°6'	35.4	76	0°45'	39.1	62	46'40"
32.8	60.3	50'	35.5	67	57'	39.3	42.22	1°17'
32.9	41	43'	35.6	56.4	1°	39.42	63.76	1°30'
33	42.5	1°19'30"	35.7	41.16	1°1'	40.8	71	43'
33	78	7°45'	35.7	55.17	1°6'	41	53	3°30'
33.15	65.5	50'	35.75	45	1°10'	41	65	1°55'
33.15	70.12	50'	35.8	44	1°12'	41.6	78	1°10'
33.35	45.09	1°19'	35.86	69	1°50'	41.9	66.5	1°18'
33.419	52.5	45'	36.3	49.19	1°12'	41.91	50.4	1°40'
33.6	59.5	1°	36.4	59	45'	42.1	65	1°10'
34	41	45'	36.4	62	1°15'	42.2	76.17	0°57'
34	51.38	9°17'	36.5	72.3	1°	42.4	59	1°3'
34	78	1°15'	36.65	67.5	1°42'	42.5	75	1°
34.1	68	55'	37	67	1°	42.5	60	52'50"

圆锥滚子

Tapered Roller



圆锥滚子外形尺寸


Tapered Roller Overall Dimension

单位Unit: μm

直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ	直径 D_w	长度 L_w	角度 φ
42.7	75.2	47'24"	46.2	66	1°55'	50	57.14	2°57'
42.8	57.2	3°45'	46.4	70	1°14'	50.4	97	1°25'
43	54	57'	46.5	52	4°	50.5	55.8	1°15'
43.1	59	58'	46.5	88	57'	50.8	71.1	29'48"
43.2	49.75	1°18'	46.6	60	45'	50.9	66	1°18'
43.3	50	1°5'	46.8	89.5	46'30"	51	59	1°20'
43.6	110	45'	46.8	98	50'	51	66	1°35'
43.8	54	2°40'	46.962	65	7°	51.58	57.2	2°
44	65	48'	47	60	1°30'	51.582	89.2	2°
44	92	1°15'37"	47.1	89.5	44'5"	51.7	60	50'
44.3	63.14	43'	47.15	52	1°55'	51.8	69	50'
44.5	73.5	45"	47.4	68.16	46'	52	66	1°8'
44.6	100	1°16'	47.6	48.46	2°12'	52	66	1°8'
44.6	54	1°	47.8	66.1	0°3'	52.4	82	1°25'
44.6	60	1°	47.963	87	0°48'	52.6	53	3°
44.6	86	55'	48	60	1°15'	52.8	78.3	2°30'
44.7	49	43'12"	48	90.19	0°55'	52.85	85	50'
44.7	81	1°6'	48.3	104	1°16'	52.89	64.23	1°
44.9	65	0°48'	48.4	65	1°5'	52.9	98.5	0°58'
45	65.737	3°45'	48.6	51.19	55'	53.6	75	1°10'
45	81.18	0°55'	48.6	72	1°10'	53.7	69	1°
45.1	77.5	2°	48.82	56	47'	53.8	107.2	56'50"
45.2	62	1°22'	48.96	88	1°	54	58	1°5'
45.5	52.8	1°25'	49	65	1°30'	54	66	2°31'
45.75	68	1°30'	49.3	59	1°13'	54	96.2	1°50'
45.9	69	58'	49.486	58.73	1°50'	55	76	34'55"
46	100	1°18'	49.5	73	1°45'	55.3	100	1°31'
46	64	45'	49.7	95.71	56'50"	56	75	1°1'
46.2	49.3	1°29'	49.8	52	48'	56	86	1°

圆锥滚子

Tapered Roller



圆锥滚子外形尺寸

Tapered Roller Overall Dimension

单位Unit: μm

直径 D_w	长度 L_w	角度 ϕ	直径 D_w	长度 L_w	角度 ϕ	直径 D_w	长度 L_w	角度 ϕ
56.3	65.5	2°30'	68.8	92.58	1°55'			
57.6	64	2°43'	69.7	88	3.24°			
57.8	70	1°5'	69.89	89.3	1°32'			
58.2	75	1°3'	70.1	103	1°46'			
58.4	122	1°37'	71.2	124.31	59'			
58.5	62	2°35'	72	78	2°40'			
59.3	89.56	2°10'	72.8	70.59	1°30'			
59.4	68.79	1°8'	73.2	71.3	2°15'			
59.9	114.3	46'35"	75	88.3	1°43'			
60	90.22	0°51'	76.1	123.35	1°3'			
60.2	101.36	1°22'	76.4	80.58	1°45'			
60.3	74	1°45'	76.5	177.76	8°15'			
60.8	74.02	1°57'	77	92	1°45'			
61	112	58'	77.1	95.5	1°30'			
61	95.47	1°45'	77.9	110	1°5'			
61.7	82	1°20'	79.3	87	2°10'			
62.2	109	1°	80	108.5	1°45'			
62.5	118	7°10'	82.7	86.5	1°40'			
63	70	1°49'	83	86.5	1°40'			
63.8	106.48	1°44'	85	95	1°10'			
63.9	75	1°20'	86.5	140	6°30'			
64.52	120	59'	88	110	1°30'			
64.9	78.5	1°45'	93.5	120	1°31'			
65.1	97	1°20'	93.6	124	1°5'			
65.5	68.36	1°15'	99.3	125.69	1°35'			
65.9	80	1°15'	102.5	113.3	1°12'			
66	83.7	10°13'	103.15	140	1°18'			
67.059	94	1°10'	105.71	170.2	1°55'			
68.6	68.6	1°15'	133.839	154.2	1°2'			

除以上规格产品，我公司可定制直径 $\phi 11\text{mm} \sim \phi 200\text{mm}$ ，长度 $\leq 250\text{mm}$ 滚子，具体咨询CHG技术部门。

In addition to the above specifications products, our company can customize the diameter $\phi 11\text{mm} \sim \phi 200\text{mm}$, length $\leq 250\text{mm}$ roller, consult CHG technical department for details.